



# Brighter LED Lighting Co.,Ltd.

Add:No. 3, Shengjing Road, Songxia industrial zone, Songang, Nanhai District, Foshan City, Guangdong Province,China

Tel : +86-0757-81635176, Fax:+86-0757-85221719, Web.:www.brtled-light.com Email:sales01@brighterledlighting.com

## LED LIGHT BARS



### BRTLED Straight Light Bars

ITEM NO.	PICTURE	DESCRIPTION	Application
  BL0210RGB	 	LEDs: 2pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 20W</b> Size: 110*83*60mm (4.3") Luminous flux: 1800lm Beam pattern: Flood/Spot Beam Housing:6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b>	
  BL0410RGB	 	LEDs: 4pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 40W</b> Size: 190*83*60mm (7.5") Luminous flux: 3600lm Beam pattern: Flood/Spot Beam Housing:6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b>	
  BL0810RGB	 	LEDs: 8pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 80W</b> Size: 350*83*60mm (13.8") Luminous flux: 7200lm Beam pattern: Flood/Spot/Combo Beam Housing:6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b>	
  BL1210RGB	 	LEDs: 12pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 120W</b> Size: 510*83*60mm (20.1") Luminous flux:10800lm Beam pattern: Flood/Spot/Combo Beam Housing:6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b>	

  BL1610RGB		<p>LEDs: 16pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 160W</b> Size: 670*83*60mm (26.4") Luminous flux:14400lm Beam pattern: Flood/Spot/Combo Beam Housing:-6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b></p>	
  BL2010RGB		<p>LEDs: 20pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 200W</b> Size: 830*83*60mm (32.7") Luminous flux:18000lm Beam pattern: Flood/Spot/Combo Beam Housing:-6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b></p>	
  BL2410RGB		<p>LEDs: 24pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 240W</b> Size: 990*83*60mm (39") Luminous flux:21600lm Beam pattern: Flood/Spot/Combo Beam Housing:-6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b></p>	
<b>BRTLED Curved Light Bars</b>			
ITEM NO.	PICTURE	DESCRIPTION	Application
  BL1210RGB-C		<p>Curved Light Bar LEDs: 12pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 120W</b> Size: 510*83*60mm (20.1") Luminous flux:10800lm Beam pattern: Flood/Spot/Combo Beam Housing:-6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R112/R10</b></p>	
  BL1610RGB-C		<p>Curved Light Bar LEDs: 16pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 160W</b> Size: 670*83*60mm (26.4 inch) Luminous flux:14400lm Beam pattern: Flood/Spot/Combo Beam Housing:-6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b></p>	



  BL2010RGB-C	  	<b>Curved Light Bar</b> LEDs: 20pc*10W (Cree XM-L2) Voltage:9-36V DC Power: 200W Size: 830*83*60mm (32.7") Luminous flux:18000lm Beam pattern: Flood/Spot/Combo Beam Housing: 6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span Deutsch Connector available <b>Approval: CE, ECE R10</b>	
  BL2410RGB-C	  	<b>Curved light bar</b> LEDs: 24pc*10W (Cree XM-L2) Voltage:9-36V DC <b>Power: 240W</b> Size: 990*83*60mm (39inch) Luminous flux:21600lm Beam pattern: Flood/Spot/Combo Beam Housing: 6063 extruded Aluminum heat-sink Front cover:Lexan polycarbonate(PC) front cover <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> Mounting accessories: Stainless steel IP Rate:IP68 Waterproof Life Time:50,000+ Hours life span <b>Approval: CE, ECE R10</b>	
  BL3210RGB-C	  	<b>Curved light bar</b> LEDs: 32pc*10W (Cree LED) <b>Actual power: 320W</b> Voltage:9-36V DC Width: around 1300mm (51 inch) Raw Luminous flux: 24500lm Available light beam: spot, flood,combo Housing: Extruded Aluminum Front cover: PC Mounting accessories: bottom/Side bracket <b>ETM Technology</b> <b>TIR Optical Lens: Light transmittance&gt;95%</b> IP68 ,CE 50,000+ Hours life span <b>Approval: CE, ECE R10</b>	 <a href="http://www.brtled-light.com">www.brtled-light.com</a>

**Remarks:**

- 1.Price Term: Ex-Factory Price. (Total Amount >USD10000 on FOB Guangzhou basis)
- 2.MOQ: No MOQ for sample order, after sample order 100pcs/model
- 3.Delivery time: 7-15 working days after sample payment.
- 4.Payment Terms: 30% of payment as deposit, balance should be received before shipment.
- 5.Payment methods: T/T and Paypal are available.
- 6.Packing: Factory Neutral Packaging

